



Smart LED Lighting

120W HV


LED Retrofit Kits



Suitable for Outdoor Pole/Arm-Mounted Area and Roadway Luminaires.

Features & Benefits:

- Built-in Surge Suppressors & Transient Protection
- High Power Factor UL Listed LED Driver
- 5-Years / 50,000 Hours (*) Warranty
- Bright • High CRI
- Low THD



Model	Product	Size	Power	Flux	Equivalent
LRK-120W-57KC-HV	120W 5,700K LED Retrofit Kit	<u>LED Engine</u> (L) 6 7/8" (W) 5" (D) 2 3/8"	120W	12,960 Lumen	600W MH or HPS




• Rated Voltage: 200-480Vac ~50/60Hz • P.F. > 0.9 • >100lm/W • CRI ≈ 70 •
 •(*) Rated Life 50,000 Hrs. (L₇₀ B₅₀) at T_[A] 25°C Max. • Beam Angle 90° • Pigtail Wire/Cable LED Driver to Mains •



Smart LED Lighting

120W HV

LED Retrofit Kits



Size / Dimensions
LED Engine
 (L) 6 7/8" x (W) 5"
 (D) 2 3/8"

Model	Product	Power	Equivalent
LRK-120W-57KC-HV	120W 5,700K LED Retrofit Kit	120W	600W MH &/or HPS Lamp
Input Voltage	Power/Power Factor	Efficacy	Flux
200-480Vac ~50/60Hz	125W Max. P.F. > 0.9	>100 lm/W	12,960 Lumen
Color Rendering	Color Temperature	Beam Angle	Life
CRI ≈ 70	5,700K CCT ±10%	90°	50,000 Hours (L ₇₀ B ₅₀) T _[A] 25°C Max.