



4 ft. 12W T8 LED Tubes

T8 & T12 Fluorescent Replacements

Dual Mode Internal Driver (UL Type A & Type B)

Features & Benefits:

- Low Energy, High Lumen per Watt
- No Ballast for Cost & Power Saving
- Ballast Compatible & Direct Wire.
- Low Temp. Instant Start
- Flicker Free Lighting
- Shatter Proof Design
- Rated Life 50,000 Hours (*)
- Color Temp. 3000K, 4000K, 5000K



Model	Product	Size	Power	Flux	Equivalent
F32T8D-12W-50K-DBD	T8 LED Tube 4ft 12W 5000K Frosted	4ft. T8 120~150° Beam Spread	12W Typ.	1,680 Lumen	F32T8/12 28W & 32W
F32T8D-12W-40K-DBD	T8 LED Tube 4ft 12W 4000K Frosted	4ft. T8 120~150° Beam Spread	12W Typ.	1,680 Lumen	F32T8/12 28W & 32W
F32T8D-12W-30K-DBD	T8 LED Tube 4ft 12W 3000K Frosted	4ft. T8 120~150° Beam Spread	12W Typ.	1,573 Lumen	F32T8/12 28W & 32W

- 120~277Vac ~50/60Hz • P.F. > 0.95 • THD <20% • Medium Bi-pin Base (G13) • Efficacy >130lm/W • CRI >80 •
- (*) Rated Life > 50,000 Hrs. (L₇₀ B₅₀) at T_[A] 45°C Max. • CCT 5000K (50K), 4000K (40K) or 3000K (30K) ±10% •
- "Equivalent." ÷ Comparable Equivalence to Fluorescent T8/T12 Wattage •