



2 ft. 12W T8 LED Tubes

T8 & T12 Fluorescent Replacements

Dual Mode Internal Driver (UL Type A & Type B)

Features & Benefits:

- Low Energy, High Lumen per Watt
- No Ballast for Cost & Power Saving
- Ballast Compatible & Direct Wire.
- Low Temp. Instant Start
- Flicker Free Lighting
- Shatter Proof Design
- Rated Life 50,000 Hours (*)
- Color Temp. 3000K, 4000K, 5000K



Model	Product	Size	Power	Flux	Equivalent
F16T8D-8W-55K	T8 LED Tube 2ff. 8W	2 FT. (60 CM)	8W	1,000 lm	F17T8 17W
F16T8D-8W-40K	T8 LED Tube 2ft. 8W	2 FT. (60 CM)	8W	960 lm	F17T8 17W
F16T8D-8W-30K	T8 LED Tube 2ft. 8W	2 FT. (60 CM)	8W	880 lm	F17T8 17W

- 120~277Vac ~50/60Hz • P.F. > 0.95 • THD <20% • Medium Bi-pin Base (G13) • Efficacy >130lm/W • CRI >80 •
- (*) Rated Life > 50,000 Hrs. (L₇₀ B₅₀) at T_[A] 45°C Max. • CCT 5000K (50K), 4000K (40K) or 3000K (30K) ±10% •
- "Equivalent." ÷ Comparable Equivalence to Fluorescent T8/T12 Wattage •